

Technical sheet :

# 2-HOOK JIB

---



## Benefits

- Robust solution for handling suspended loads.
- Jib fitted with 2 hooks to meet various needs of building sites.
- Adaptability for all yard handling applications

## Technical characteristics

- 2 capacity / outreach couples
- Safety: homologated swivel self locking hook.

Capacities		P 4000	P 6000
Max. outreach (mm)	I4	708	808
Capacity (kg)		4000	6000
Capacity 2 (kg)		1200	2000
Max @ outreach 2 (mm)		2708	2708
Weight and dimensions			
Overall height (mm)	h17	625	625
Width (mm)		830	830
Length (mm)		2838	2838
Overall weight (kg)		210	282
Working Parameters			
Machine Equipment		No predisposition required	No predisposition required
Hydraulic system		false	false

Machines compatibility	P 4000	P 6000
<b>Reference Number</b>	<b>653226</b>	<b>-</b>
MT 733 Easy	X	-
MT 933 Easy	X	-
MT 1033 easy	X	-
MT 1135	X	-
MT 1135 H easy ST5	X	-
MT 1135 HA Easy ST5	X	-
MT 1135 easy ST5	X	-
MT 1440	X	-
MT 1440 A	X	-
MT 1440 HA	X	-
MT 1440 easy ST5	X	-
MT 1840	X	-
MT 1840 A	X	-
MT 1840 HA	X	-
MT 1840 easy ST5	X	-
MT-X 733	X	-
MT-X 1033	X	-
MT-X 1440	X	-
MT-X 1440 A	X	-
MT-X 1840	X	-
MT-X 1840 A	X	-
<b>Reference Number E-RECO</b>	<b>921321</b>	<b>921322</b>
MRT 1440 Easy T4 S1 400°	X	X
MRT 1440 Easy T4 S2 400°	X	X
MRT 1640 Easy T4 S1 360°	X	X
MRT 1640 Easy T4 S1 400°	X	X
MRT 1640 Easy T4 S2 360°	X	X
MRT 1640 Easy T4 S2 400°	X	X
MRT 1840 Easy T4 S1 360°	X	X
MRT 1840 Easy T4 S1 400°	X	X
MRT 1840 Easy T4 S2 360°	X	X
MRT 1840 Easy T4 S2 400°	X	X
MRT 2145 Easy T4 S1 360°	X	X
MRT 2145 Easy T4 S1 400°	X	X
MRT 2145 Easy T4 S2 360°	X	X
MRT 2145 Easy T4 S2 400°	X	X
MRT 2150 Privilege Plus	X	X
MRT 2470 Privilege Plus	X	X
MRT 2545 Easy T4 S1 360°	X	X
MRT 2545 Easy T4 S1 400°	X	X
MRT 2545 Easy T4 S2 360°	X	X

Machines compatibility	P 4000	P 6000
MRT 2545 Easy T4 S2 400°	X	X
MRT 2550 Privilege Plus	X	X
MRT 3050 Privilege Plus	X	X
MRT 3255 Privilege Plus	-	X
MRT-X 1440 Easy 400°	X	X
MRT-X 1640 Easy 360°	X	X
MRT-X 1640 Easy 400°	X	X
MRT-X 1840 Easy 360°	X	X
MRT-X 1840 Easy 400°	X	X
MRT-X 2145 Easy 360°	X	X
MRT-X 2145 Easy 400°	X	X
MRT-X 2150 Privilege Plus	X	X
MRT-X 2470 Privilege Plus	X	X
MRT-X 2545 Easy 360°	X	X
MRT-X 2545 Easy 400°	X	X
MRT-X 2550 Privilege Plus	X	X
MRT-X 3050 Privilege Plus	X	X
MRT-X 3255 Privilege Plus	-	X



Siège Social  
430 rue de l'Aubinière - 44150 Ancenis Cedex - France  
Tel: +33(0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97  
[www.manitou.com](http://www.manitou.com)



This brochure describes versions and configuration options for Manitou products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Manitou reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Manitou dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Manitou and may not be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,547,824 euros - 857 802 508  
RCS Nantes