

Characteristics



Static
Dissipating



HEPA -
Included



Detachable
Tank



Dry Recovery



SS 430



High Filtration
Efficiency Unit



- HEPA filter with an efficiency of 99.995% at 0.3 micron. Tested IEST-RP-CC001. H14 by MPPS method as per EN 1822 and OSHA compliant. All of our HEPA vacuum systems are aerosol leak tested before leaving our facility - included
- Designed for general cleaning in the Food industry
- Heavy duty 2-stage by-pass motor
- Manual Filter Shaker (MFS) system
- For dry recovery only
- Heavy duty powder coated body and stainless steel recovery tank
- Detachable recovery tank (DT) for easy disposal of recovered materials
- Equipped with a 4-wheel cart and tool basket. Cart has static dissipative or conductive wheels
- Includes a complete tool kit with a clear suction hose. A variety of optional accessories are available including autoclavable and ESD safe hoses and tools

Specifications

2D-25L (DT) MFS WT SERIES	111401B	111403B
Model Name	2D-25L (DT) MFS WT NO HEPA	2D-25L (DT) MFS WT HEPA
Type (Powerhead)	Electric	Electric
Tension	230 V	230 V
Frequency	50 Hz	50 Hz
Phase	Single	Single
Wattage	1200 W	1200 W
Power	1.2 kW	1.2 kW
Amperage	5 A	5 A
Air Flow	153 m ³ /h	153 m ³ /h
Vacuum Pressure	2030 mm H ₂ O	2030 mm H ₂ O
Sound Level	75 dB(A)	75 dB(A)
Type of Power Outlet	European	European
Suction Inlet	50 mm	50 mm
Cart Type	Detachable Tank (DT)	Detachable Tank (DT)
Filter Cleaning	Manual Filter Shaker (MFS)	Manual Filter Shaker (MFS)
Dust Recovery Tank	24.6 L	24.6 L
Length	58 cm	58 cm
Width	53 cm	53 cm
Height	102 cm	102 cm
Weight (Vacuum Only)	23 kg.	23 kg.
Cord Length	10.6 m	10.6 m

Please note that specifications are subject to change without notice

Use only recommended tools & accessories



HEPA Filter - Included



Clear Polyliner Recovery Bags - Included



Ø1.5" (Ø38 mm) Tools and Accessories - Included



25L Detachable Tank