


5015 Max. 7,8 W

AC/DC PLUG-IN ADAPTER REGULATED



- Max. 7,8 W output power
- 230 VAC input voltage
- Fixed output voltages from 4,5 to 12V
- Compliance with relevant worldwide safety standards
- Available with EU or UK terminals. (UK: 12v only)
- Exchangeable output plugs, providing:
 - reduced stocking requirements
 - short delivery lead times
 - snap-locks for added safety



<u>Technical specifications</u>	
<i>Input voltage:</i>	230 VAC ± 10%, 50 Hz
<i>Temperature range:</i>	-10°C to +40°C
<i>Protection:</i>	Thermal fuse in transformer
<i>Insulation class</i>	II
<i>Electrical safety</i>	EN 60950
<i>EMC, Emission</i>	EN 61000-6-3
<i>EMC, Immunity</i>	EN 61000-6-1
<i>Mains connections:</i>	EU or UK
<i>Output terminals:</i>	Secondary cable w/snap-on plug
<i>Dimensions UK (LxWxH):</i>	82x57x49mm
<i>Dimensions EU (LxWxH):</i>	78x58x48mm
<i>Weight:</i>	UK: 490g, EU: 470g

Survey of Voltage versions

Output Voltage (VDC)	Load current (mA)	Output power (W)
4,5	1200	5,4
6	1200	7,2*
7,5	1000	7,5*
9	800	7,2*
12	650	7,8

* Sec. Switch