

PONSSE H8HD

TOUGH PERFORMANCE

PONSSE H8 HD is a tough-built harvester head with high power and excellent geometry for the most demanding logging operations. It is designed for the hard use on tracked base machines, featuring a heavy-duty frame structure and efficient hydraulic system to ensure high reliability and performance.







PONSSE H8 HD is a havey-duty harvester head for felling and processing both hardwood and softwood trees in difficult conditions. Strong grip, powerful feeding and fast sawing are packed in a

robust and reliable package that can be fitted to various tracked carriers. Reinforced frame and tilt arm provide the strength needed in tough

operations. Wide feed roller geometry supports even the large stems with feed rollers instead of delimbing blades. This allows using lower pressure on knives, which improves fuel economy, feeding speed and measuring accuracy. Optimal tilt pivot geometry minimizes the upwards torque of the head, giving smoother feeding and better

PONSSE Opti control system is designed spe-

justments and settings work perfectly together

with the head, offering easy but versatile func-

tions to perfectly fit the base machine and work

follow-up for overall production with either manual

The PONSSE H8 HD is available with a top saw for processing curvy trees with multiple branches. Processing delimbing knives are longer than standard knifes in order to make it easier when

requirements. PONSSE systems offer mobile

or automatic data transfer.

picking logs out from a pile.

cifically for PONSSE harvester heads. All ad-

grip of the tree.



740 mm (29.2 in)





36 kN (8,093 lbf)







1,650 mm (65 in) -

3 rollers

4+1+1

20 tons

36 kN (8.093 lbf)

5 m/s (16.4 ft/s)

28 MPa (4,061 psi)

Largest opening (feeding rollers): 740 mm (29.2 in)

Maximum opening of front knives: 740 mm (29.2 in) Maximum opening of rear knives: 780 mm (31 in) Delimbing knives and feeding rollers are separately controlled.

Plenty of optional equipment is available in addition to the comprehensive PONSSE H8 HD standard equipment. Consult your nearest Ponsse Service Center or dealer for more information on

FEEDING UNIT

Feeding system:

Feeding force:

Feeding speed:

DELIMBING UNIT

TRACKED CARRIER Operating pressure:

Carrier weight (min):

OPTIONAL EQUIPMENT

the standard and optional equipment.

Number of knives:



720 mm (29.2 in)



from 1,650 kg (3,638 lbs)



36 kN (8,093 lbf)



(24 in)

H8 HD TOP SAW

HB HD

MEASUREMENTS

Weight: H8 HD: from 1,450 kg (3,196 lbs) excl. rotator H8 HD top saw: from 1,650 kg (3,638 lbs) excl. rotator

H8 HD: 1.560 mm (61 in) Length:

H8 HD top saw: 1.765 mm (69 in)

Width: 1.650 mm (65 in) Height without rotator: H8 HD: 1,690 mm (66 in)

H8 HD top saw: 1,910 mm (75 in)

| SAW UNII | |
|--------------------|---------------------------|
| Hydraulic chainsaw | |
| Saw motor: | 30/32cc |
| Saw bar length: | 820/900 mm (32/35 in) |
| Cutting diameter: | 720/800 mm (28.3/31.5 in) |
| Chain: | 0.404" |

TOP SAW

| TOP ONT | |
|---------------------------|----------------|
| Saw motor: | 19cc |
| Top saw bar: | 750 mm (30 in) |
| Top saw cutting diameter: | 600 mm (24 in) |
| Top saw chain: | 0.404" |

Technical and specifications details may vary in different installations.

These can be related to carrier, base machine or Ponsse Harvester installations.

Ponsse Plc

Ponssentie 22 FI-74200 Vieremä **FINLAND** Tel. +358 20 768 800

www.ponsse.com

4 Annan Business Park Annan Dumfriesshire

Ponsse UK Ltd.

DG12 6TZ

UNITED KINGDOM Tel. + 44 1461 207 510 Tel. +353 57 863 3762

Ponsse Machines Ireland Ltd

Cappakeel, Emo Portlaoise R32NN28 Laois **IRELAND**

Ponsse North America, Inc. 4400 International Lane Rhinelander, WI 54501 USA Tel. +1 715 369 4833 Fax +1 715 369 4838

PONSSE

A logger's best friend www.ponsse.com

Images are for illustration purposes only.