



CopperLink™ Ruggedized Ethernet Extender Model CL1314R

Use the CopperLink 1314R Ruggedized Ethernet Extender to interconnect remote LANs or network enabled device up to 3.4 miles apart using single-twisted-pair cabling—and realize the best-possible speed/distance combination in the industry!

High Speed Extension

Achieve speeds up to 5.7 Mbps.

Multi-rate Selection

Just plug the units in and select the ideal user-configurable rate for your application.

CopperLink 2-Wire Connection

Easy 2-wire CopperLink connection via built-in RJ-45 port.

Ruggedized

Operating temperature of -40 to 85°C and optional conformal coating to protect against condens-ing humidity and corrosion.

Hardened

Aluminum enclosure designed to meet IP40 specifications; DIN rail mount included

Extended Temperature

-40 to 85°C operation.

Transparent LAN Bridging

Transparently pass higher-layer protocols with support for 802.1Q VLAN tagging.

Automatic Learning, Aging, and Filtering

Keeps local traffic local, ensuring efficient utilization of the long-range link.

Ethernet extension doesn't have to be expensive or difficult. The CL1314R Ruggedized Ethernet Extenders open the door to cost-effective Ethernet extension that is easy to set up. Featuring plug-and-play installation, the CL1314R CopperLink Ethernet Extenders leverage existing copper twisted-pair infrastructure to interconnect Ethernet devices and networks at high speeds over long distances.

Operating over standard 0.5 mm (24 AWG) voice-grade wiring, the CL1314R delivers speeds up to 5.7 Mbps and extends Ethernet connections across distances ranging from 2.7 to 6.9 km (1.7 to 4.3 miles). Whether you need connect to a remote office or private-network backbone to a corporate LAN—or interconnect such network-enabled devices such as PCs, digital sensors and IP cameras—Patton Ethernet Extenders offer the industry's optimum combination of speed and distance.

Patton's CopperLink Ethernet Extenders ensure hassle-free set-up and operation, while achieving the highest possible line rate for the required distance and electro-magnetic environment. Users "hard-set" the desired line rate via DIP switches or console Telnet.

The CL1314R comes with a built-in two-port, auto-sensing, 10/100Base-TX Ethernet switch that provides automatic medium-dependent interface crossover capability (auto-MDIX). That means you can use cross-over or straight-through cables (whichever is handy) to connect up to four Ethernet devices. The auto-MDIX feature detects the polarity of the cabling on each port, and automatically configures the signaling to match. Absolutely no user-configuration is required.

Operating at layer 2 of the OSI model (data link layer), the CL1314R transparently passes all higher-layer protocols—including VLAN tagging, multicast addressing, VPN pass-through for IPsec, and all IP-video compression schemes. All common industrial protocols are also transparently supported, including MODBUS/TCP and PROFINET IO.

Set-up is easy! Simply connect up to four LAN devices to the Ethernet switch, plug the copper twisted-pair into each extender, and apply power! For simple, cost-effective and efficient Ethernet extension, Patton's CopperLink Ethernet Extenders are the ideal solution!

For more information, visit www.patton.com.

Distance on 24 AWG (0.5mm)			
Line Rate	K Feet	Miles	km
192	22.5	4.26	6.9
256	22.5	4.26	6.9
512	22.1	4.18	6.7
768	19.5	3.69	5.5
1024	18.5	3.50	5.6
1280	18.5	3.50	5.6
1536	18.6	3.50	5.6
2048	16.5	3.13	5.03
2304	16.5	3.13	5.03
4608	11	2.08	3.35
5696	9	1.70	2.74



Typical Application

Extend 10/100Base-TX Ethernet to reach beyond its natural limitations



Model CL1314R ruggedized Ethernet Extenders are ideal for delivering Ethernet links to remote buildings that are beyond the 328-foot (100-meter) distance limit of Ethernet. The 5.7 Mbps throughput eliminates bandwidth concerns previously experienced with other copper wired transmission technologies.

The CL1314R includes several user configurable line rates so that a user will get a consistent link, even in noisy environments. By utilizing existing voice-grade copper pairs or legacy serial circuits the expense and hassle of installing low capacitance or fiber cable is no longer required.

• Plug-and-Play

Just unpack a pair of extenders and plug in the cables. Apply power and your connection is up and running. It just doesn't get any easier!

• High Speed/Long Reach

The CL1314R Ethernet extender provides the industry's ultimate combination of speed and distance!

Specifications

Protocol Transparent to higher layer protocols	Line Coding TC-PAM 16 for rates from 192 to 2.3 Mbps; TC-PAM 32 for rates above 2.3 Mbps	MTBF 4.7 years	Altitude 0 to 15,000 ft (0 to 4,600 m)
Transmission Line Single twisted pair	Connectors RJ-45 on copper line side and 2 x 10/100 Ethernet, terminal block power connector	Power External 90–260 VAC, 50–60 Hz (Universal Input)	Enclosure Aluminum (designed to meet IP40)
Line Rates Rates from 192 kbps to 5.7 Mbps, selectable in all 64 kbps increments up to 5.7 Mbps	Line Interface Transformer coupled, 1500 VAC isolation	Power Consumption 0.8A@5V	Dimensions 2.25W x 5.62H x 4.66D in. (5.7W x 14.27H x 11.83D mm)
Front Panel LED Status Indicators WAN: Link, LAN (Ethernet): Link/Act, Power	Management DIP switch, Telnet console	Operating Temp. -40 to 185°F (-40 to 85°C)	Weight 0.7 lbs (0.30 kg)
		Humidity 5 to 95%, non-condensing	Compliance FCC Part 15A, CE Mark per EMC directive 89/336/EEC and Low Voltage Directive 73/23/EEC

* Specifications subject to change without notice.

PATTON[®]
Let's Connect![™]

Patton Electronics Co.
7622 Rickenbacker Drive
Gaithersburg, Maryland 20879
USA
Phone +1 301 975 1000
Fax +1 301 869 9293
E-mail sales@patton.com
Web www.patton.com

Patton-Inalp Networks AG
Meriedweg 7
CH-3172 Niederwangen
Switzerland
Phone +41 (31) 985 25 25
Fax +41 (31) 985 25 26
E-mail sales@inalp.com
Web www.inalp.com

Patton Hungary Zrt
Gábor Dénes utca 4.
Infopark Building C
Budapest H-1117
Hungary
Phone +36 1 439 4840
Fax +36 1 439 4844
E-mail ce@patton.com
Web www.patton.com

07MCL1314R-DS3

Patton is a registered trademark, and CopperLink and Let's Connect! are trademarks of Patton Electronics Company in the United States and other countries.